

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 November 2001 (08.11.2001)

PCT

(10) International Publication Number
WO 01/82813 A2

(51) International Patent Classification⁷: **A61B 18/14**

55125 (US). TRESCONY, Paul, V.; 11648 Oakview Court, Champlin, MN 55316 (US). JAHNS, Scott, E.; 923 3rd Street, Hudson, WI 54016 (US).

(21) International Application Number: PCT/US01/12628

(22) International Filing Date: 18 April 2001 (18.04.2001)

(74) Agent: BAUER, Stephen, W.; Medtronic, Inc. LC340, 710 Medtronic Parkway, Minneapolis, MN 55432 (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/558,975 27 April 2000 (27.04.2000) US

(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(71) Applicant: MEDTRONIC, INC. [US/US]; 710 Medtronic Parkway Northeast, Minneapolis, MN 55432 (US).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


(72) Inventors: FRANCISCHELLI, David, E.; 744 Benton Street, Anoka, MN 55303 (US). COMBEN, Richard, H.; 2832 Woodcrest Drive, St. Paul, MN 55112 (US). HOEY, Michael, F.; 5733 Pond Drive, Shoreview, MN 55126 (US). MEHRA, Rahul; 4980 Neal Avenue North, Stillwater, MN 55082 (US). OCEL, Jon, M.; 573 10th Avenue S.W., New Brighton, MN 55112 (US). PEARSON, Robert; 2134 Wallingford Lane, Woodbury, MN

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: VARIABLE LENGTH ELECTRODES FOR DELIVERY OF IRRIGATED ABLATION



10

(57) Abstract: A device for ablating tissue is provided. The device comprises a conductive element with a channel for irrigating fluid formed therein, which is in contact with a non-conductive microporous interface. All or a portion of the interface may be removable. When the interface is removed, a portion of the conductive element is exposed for use in ablating tissue. Methods of using the device and for removing the interface are also provided.



WO 01/82813 A2

WO 01/82813 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

VARIABLE LENGTH ELECTRODES FOR DELIVERY OF IRRIGATED ABLATION

5

FIELD OF THE INVENTION

This invention relates to ablation devices that are used to create lesions in tissue. More particularly, this invention relates to conductive elements for use in such devices which vary in length and which incorporate improved methods of irrigation delivery.

10

BACKGROUND OF THE INVENTION

15

The action of the heart is known to depend on electrical signals within the heart tissue. Occasionally, these electrical signals do not function properly. The maze procedure is a surgical operation for patients with chronic atrial fibrillation that is resistant to medical treatment. In this procedure, incisions are created in the right and left atria to produce an orderly passage of the electrical impulse from the SA node to the atrioventricular node. Blind passageways are also created to suppress reentry cycles. Currently, the lesions may still be created using a traditional cut and sew technique. The scar tissue resulting from the procedure results in a non-conductive lesion.

20

Ablation of cardiac conduction pathways in the region of tissue where the signals are malfunctioning is now being used to replace the surgical incisions. Ablation is also used therapeutically with other organ tissue, such as the liver, prostate and uterus. Ablation of organic tissue is also used in several surgical procedures, for both diagnosis and therapy.

25

30

In one type of procedure, one or more electrodes at the tip of an electrophysiology ablation device allow the physician to measure electrical signals along the surface of the heart (mapping). When necessary, in another type of procedure, the physician can also ablate certain tissues using, typically, radio frequency (RF) energy conducted to one or more ablation electrodes. During tissue ablation, energy is used to create lesions in the tissue for different purposes. High levels of energy are used to cut and remove tissue (electrosurgery). Lower levels of energy are used to cause cell damage but leave the structure intact so that electrical pathways are blocked within the tissue.

A variety of devices, such as catheters, are used to ablate tissue. Typically, such devices include a conductive tip, which serves as one electrode in an electrical circuit. The electrical circuit is completed via a grounding electrode that may also be on the device or may be coupled to the patient. By controlling the level of energy transmitted to the electrode, the surgeon is able to control the amount of heat generated for the purposes described above.

Irrigation of the ablation site cools the electrode. Irrigated ablation is also known to create deeper lesions that are more likely to be transmural. Transmurality is achieved when the full thickness of the target tissue is ablated.

During ablation, irrigation of the ablation site helps to cool the ablation electrodes, thereby reducing overheating in the vicinity of the electrodes. Undesirable consequences of overheating include the excessive coagulation of blood and the unintended destruction of healthy tissue adjacent the ablation site. The efficient cooling of the linear ablation electrode permits longer lesions to be created by permitting higher ablation energy without resulting in excessive electrode heating.

Typically, delivery of irrigation to the site is accomplished using a separate irrigation source which may pump into the ablation device or which may pump directly to the target tissue site. This requires a separate device that may not deliver irrigation as site-specifically as desired.

Furthermore, there is relatively high hydraulic impedance to saline flow at the distal end (towards ablation site) of a typical ablation device. In comparison, the hydraulic impedance to flow is lower at the proximal end (towards user) of the device. This sometimes results in more irrigation fluid being distributed at the proximal end than at the distal end.

Additionally, there may also be difficulties with electrical impedance to saline flow in a typical ablation device. This may be particularly true in a hemostat-type ablation device. In such a device, the target tissue is positioned between the two jaws of the hemostat, both of which carry ablation electrodes. If the tissue is shorter than the length of the hemostat jaws, a saline bridge may form between the hemostat jaws due to the surface tension of the fluid. This saline bridge is a low electrical impedance pathway. Electrical flow may, therefore, occur preferentially towards the bridge and yield unreliable ablation.

Irrigation fluid may also not be evenly distributed along a single electrode because of the impedance factors described above. Uneven distribution of fluid may result in an uneven lesion. In some cases, the tissue may not receive any irrigation in some areas. The electrode may contact the surface of the target tissue in these unirrigated areas, causing sticking or even charring.

Additionally, longer electrodes are sometimes desired to create longer lesions. These electrodes have a larger pressure drop along their length. This results in greater fluid flow from the proximal end than the distal end and thus irrigation is unevenly distributed which may result in sticking of the ablated tissue to the electrode. Currently an electrode of a given length is needed to create a lesion of a given length. If a lesion of a different length is desired, a new electrode must be used.

It would be desirable therefore to provide a means to control and vary irrigation.

It would further be desirable to facilitate control of lesion length.

It would further be desirable to provide a means for evenly irrigating an ablation electrode and concomitant target tissue site.

It would further be desirable to provide a means for evenly irrigating ablation electrodes of variable length.

It would further be desirable to provide a device in which irrigation capabilities and ablation capabilities are integrated.

SUMMARY OF THE INVENTION

One aspect of the present invention provides a device for ablating organic tissue. The device includes a conductive element, a fluid component in communication with the conductive element and a non-conductive interface positioned adjacent the tissue to allow the fluid to pass through the interface and contact the tissue. The conductive element may be, for example, a metallic coil with a lumen, a spring with a lumen or a wire. The diameter of the conductive element may be greater than the diameter of the interface. The conductive element and the interface may be the same. The interface may be micro-porous. The interface may also be of a variable length and a portion of the interface may be removable. The interface may be perforated, may comprise openings that are slidably or rotatably opened. The interface may be non-conductive or conductive. The interface

may lie between the conductive element and the tissue surface. The interface may encircle the conductive element and the fluid component. The interface may be a rigid structure, a fluid saturated gel, or a micro-porous section of the fluid component. The interface and the fluid component may be the same. The fluid component may be a non-porous coating.
5 The device may also include means for flowing the fluid component through the interface, such as an infusion pump.

Another aspect of the invention provides a device for creating ablations of variable length, comprising a conductive element having a channel formed therein, the channel operatively adapted to receive irrigating fluid; and a removable non-conductive
10 interface in communication with the conductive element. The device may include a support element in communication with the conductive element. The support element may be a slotted tube. The conductive element may be a slotted tube.

Another aspect of the invention provides a device for creating ablations of variable length, comprising a non-porous tube operatively adapted to receive irrigating
15 fluid therein, a conductive element in communication with the tube and a removable non-conductive interface in communication with the conductive element. The non-conductive interface may be a portion of the non-porous tube. The non-conductive interface may be micro-porous. The non-conductive interface may be rigid.

Another aspect of the present invention provides a device for creating ablations of variable length, comprising a non-porous tube operatively adapted to receive a hydrogel, a
20 conductive element in communication with the tube and a removable non-conductive interface in communication with the conductive element. The non-porous tube may be slotted.

Another aspect of the present invention provides a method of ablating organic
25 tissue. The method includes providing a conductive element having a channel formed therein, the channel operatively adapted to receive irrigating fluid; and a removable non-conductive interface in communication with the conductive element. The method also includes removing a portion of the interface to expose a portion of the conductive element and ablating the tissue with the exposed portion of the conductive element. The interface
30 may be perforated. The interface may be disposable. The interface may be reusable. The interface may also be a removable tip.

The foregoing, and other, features and advantages of the invention will become further apparent from the following detailed description of the presently preferred embodiments, read in conjunction with the accompanying drawings. The detailed description and drawings are merely illustrative of the invention rather than limiting, the scope of the invention being defined by the appended claims in equivalence thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic view of a system for ablating tissue in accordance with the present invention;

FIG. 2 is a longitudinal schematic view of a variable length ablation electrode in accordance with the present invention;

FIG. 3 is a longitudinal schematic view of a second embodiment of a variable length ablation electrode in accordance with the present invention;

FIG. 4 is a schematic view of a cross-section of a third embodiment of a variable length ablation electrode in accordance with the present invention;

FIG. 5 is a longitudinal schematic view of a fourth embodiment of a variable length ablation electrode in accordance with the present invention;

FIG. 6 is a longitudinal schematic view of a fifth embodiment of a variable length ablation electrode in accordance with the present invention;

FIG. 7 is a schematic view of a cross-section of one embodiment of an ablation electrode in accordance with the present invention;

FIG. 8 is a schematic view of a cross-section of another embodiment of an ablation electrode in accordance with the present invention;

FIG. 9 is a schematic view of a cross-section of another embodiment of an ablation electrode in accordance with the present invention;

FIG. 10 is a schematic view of a cross-section of another embodiment of an ablation electrode in accordance with the present invention;

FIG. 11 is a schematic view of a cross-section of another embodiment of an ablation electrode in accordance with the present invention; and

FIG. 12 is a schematic view of a cross-section of another embodiment of an ablation electrode in accordance with the present invention.

DETAILED DESCRIPTION OF THE
PRESENTLY PREFERRED EMBODIMENTS

FIG. 1 shows a schematic view of one embodiment of system **10** for ablating tissue in accordance with the present invention. Typically the tissue to be ablated will be located within the body cavity, such as the endocardial or epicardial tissue of the heart. Other body organ tissue, such as the liver, can also be ablated using the present invention. System **10** may include an ablation device **20** that comprises at least one conductive element **22**, such as an electrode, and a connection **28** to a power source **30**. System **10** also may include a conduit **38** to an irrigation source **40** that provides irrigation fluid to the ablation site. System **10** may also include an insulating material **32** that may insulate conductive element **22**. Insulating material **32** may also direct delivery of energy and/or irrigation along conductive element **22**. System **10** may also include a support member **33** that may provide structural integrity to conductive element **22**. System **10** may also include an indifferent electrode **23** which may serve as the return plate for energy transmitted through electrode **22**. Electrode **23** may also be covered by insulating material and supported by a support member.

Ablation device **20** may be any suitable ablation tool such as, for example, a catheter, an electrocautery device, an electrosurgical device, a suction-assisted ablation tool, an ablation pod, an ablation paddle, an ablation hemostat or an ablation wire. Ablation device **20** and its components are preferably made of a biocompatible material such as stainless steel, biocompatible epoxy or biocompatible plastic. Preferably, a biocompatible material prompts little allergenic response from the patient's body and is resistant to corrosion from being placed within the patient's body. Furthermore, the biocompatible material preferably does not cause any additional stress to the patient's body, for example, it does not scrape detrimentally against any elements within the surgical cavity.

Preferably, ablation device **20** may be permanently or removably attached to a maneuvering apparatus for manipulating device **20** onto a tissue surface. For example, ablation device **20** may be attached to hemostat handles **12** such as shown in **FIG. 1**. Ablation device **20** may also be located on one or more of the hemostat jaws **32**. Ablation

device 20 may also be used in conjunction with a traditional catheter, for example, in a closed heart ablation procedure. Ablation device 20 may also be maneuvered with a leash or pull-wire assembly. Ablation device may also be positioned on a pen-like maneuvering apparatus such as the Cardioblate pen available from Medtronic, Inc. Alternatively any appropriate flexible or rigid handle could be used as a maneuvering apparatus.

Alternatively, any appropriate endoscopic or thoroscopic-maneuvering apparatus may also be used with device 20.

Device 20 also preferably includes a connection 28 suitable for conducting energy to device 20, particularly to conductive element 22 from a power source.

The conductive element 22 of ablation device 20 is preferably an electrode. This electrode 22 may be positioned in any suitable place on device 20. Preferably electrode 22 is placed near an end of the device 20, away from the user, to be more easily manipulated against the tissue 60 to be ablated.

System 10 may also include an indifferent electrode 23 which may serve as the return plate for energy transmitted through electrode 22.

Electrode 23 may be placed elsewhere on the patient's body than the ablation site. For example, electrode 23 may be placed on the patient's back or thigh. Electrode 23 may also serve as a second ablation electrode in a bipolar arrangement. The two electrodes 22, 23 may be arranged on the jaws of a hemostat-like tool such as shown in FIG. 1.

Electrodes 22, 23 may be arranged in other orientations to each other, such as, for example, parallel to each other on a surface.

As ablation occurs, it is sometimes desirable to irrigate the ablation site with irrigation fluid, which may be, for example, any suitable fluid such as saline or another conductive fluid. The irrigating fluid may cool the electrode 22 of ablation device 20.

Irrigated ablation is also known to create deeper lesions that are more likely to be transmural. Transmurality is achieved when the full thickness of the target tissue is ablated. Furthermore, continuous fluid flow may keep the ablation device surface temperature below the threshold for blood coagulation, which may clog the device. Use of irrigating fluid may therefore reduce the need to remove a clogged ablation device for cleaning or replacement. The presence of an ionic fluid layer between electrode 22 and the tissue to be ablated may also ensure that an ionic fluid layer conforming to the tissue

contours is created. In one preferred embodiment, saline solution is used. Alternatively, other energy-conducting liquids, such as Ringer's solution, ionic contrast, or even blood, may be used. Diagnostic or therapeutic agents, such as lidocaine, CA^{++} blockers, ionic contrast, or gene therapy agents may also be delivered before, with or after the delivery of the irrigating fluid. Irrigation source 40 may be any suitable source of irrigation fluid such as, for example, a standard irrigation pump (not shown). This pump may also be connected to power source 30 or may have its own source of power. Preferably, device 20 also includes a conduit 38 for delivering irrigation to the ablation site from irrigation source 40.

FIG. 2 shows a schematic representation of one embodiment of a variable length electrode in accordance with the present invention. Electrode 222 may be covered with an insulating material 232. Prior to ablation, insulating material 232 may be removed, for example, by rolling back towards a proximal end of electrode 222. As insulating material 232 is rolled back, ablating surface 242 of electrode 222 may be revealed. The ablating surface may be applied against a surface of tissue 260. The length of ablating surface 242 may vary, depending on the amount of insulating material 232 that is uncovered. Insulating material 232 is preferably a material that insulates the unexposed area of the electrode 222. Such an insulating material may be, for example, silicone or polyurethane. The exposed ablation surface 242 may be conductive and irrigated. However, the section of electrode 222 covered by insulating material 232 may be non-conductive. Furthermore, the section of electrode 222 covered by insulating material 232 may be formed of a material that does not allow irrigating fluid to flow through. Since the irrigating fluid does not flow through the insulated end, a saline bridge as described above may not form. Additionally, the insulating material may direct all energy so that it is delivered to the exposed portion 242 of electrode 222. Additionally, the insulating material may direct all irrigating fluid so that it is delivered to the exposed portion 242 of electrode 222. The irrigation fluid may flow within the insulating material 232 but may not flow through the material 232. Therefore, the unexposed, insulated portion of tool 20 may not be irrigated. The irrigating fluid may thereby delivered only to the desired, exposed portion 242 of electrode 222.

Insulating material 232 may then be returned to its original state to cover exposed surface 242. The same electrode 222 may then be used to ablate a shorter surface. Alternatively, insulating material may be a tip, which may be removed completely. A new insulating material may then be placed over electrode. These tips of insulating material 232 may be of variable length.

FIG. 3 shows a schematic longitudinal representation of another embodiment of the variable length electrode of the present invention. In this embodiment, insulating material 332 is perforated. In use, a user may remove insulating material 332 from segment A, thereby exposing ablation surface 342 as shown. If the user desires, a longer ablation surface in order to create a longer lesion, he may remove additional insulating material 332 from segment B. This results in longer ablation surface 343 as shown. Preferably insulating material that is removed may be disposable.

FIG. 4 shows a cross-section view of another embodiment of the variable length electrode of the present invention. In this embodiment, electrode 422 may be covered by insulating material 432 and a rotating portion of insulating material 452. Portion 432 of the insulating material may cover most of the electrode 422. Electrode 422 may remain covered by portion 432 of the insulating material along the length of the electrode. Meanwhile, portion 452 of the insulating material may be removable or movable. Preferably, portion 452 may be rotatably removable or movable. In use, portion 452 of the insulating material may be moved to uncover ablating surface 442. For example, portion 452 of the insulating material may be moved in the direction indicated by the arrow to remove the cover. Portion 452 may be moved to expose ablating surface 442 of electrode 422 along the entire length of electrode 422. Alternatively, portion 452 of insulating material may be moved to uncover ablation surface 442 only along a given portion of electrode 422. Ablating surface 442 may be used to ablate a surface of tissue 460.

FIG. 5 shows a longitudinal schematic view of the variable length electrode of the present invention. In use, the insulating material 532 shown in FIG. 5 may be formed as a series of panels that cover electrode 522. For example, three panels, A, B, and C are shown in FIG. 5. Panel A of insulating material 532 may be moved to fit over panel B of insulating material 532. Panel A may be moved, for example, in the direction indicated by the arrows. This may expose ablation surface 542 which may have originally been

covered by panel A. If the user desires a longer length electrode to create, for example, a longer lesion, the user may slide panel B over panel C and panel A over panel B to expose an even longer ablation surface 543. Ablating surface 542, 543 may be used to ablate a surface of tissue 560.

5 In the embodiments shown in FIGS. 1-5, the conductive element may preferably be a coil or spring. Alternatively, the conductive element may be metallic rod with a lumen machined into its axis, a wire braid, a wire mesh or another suitable type of electrode.

10 FIG. 6 shows a longitudinal schematic view of a conductive element 22 in accordance with the present invention. Preferably, the coil or spring may be made of a conductive material such as, for example, metal. This coil may have a lumen 24. Irrigating fluid may be flowed into the lumen 24 of coil 22. For example, irrigating fluid may be pumped from irrigation source 40. As the fluid is pumped from irrigation source 40, the fluid may weep evenly along the length of the coil, thus delivering fluid to the
15 ablation site. A support member 33 may also be incorporated into or adjacent conductive element 22. Preferably support member 33 provides conductive element 22 with additional structural rigidity. The support member 33 may be, for example, a slotted metal tube. The support member may also be made from materials, such as, for example, Nitinol or other superelastic materials, which may allow support and some malleability.

20 Slotted tube 33 may be formed of a slightly smaller diameter than coil 22. In this case, a portion of coil 22 may protrude through the slot of tube 33 as shown at 630. This protruding of coil 22 may occur along the length of electrode 22. Alternatively, this protruding may occur at a given area of electrode 22. This protrusion may help coil 22 conform to the surface of tissue 660 to be ablated.

25 Preferably, the pitch or tightness of the coil of conductive element 22 may determine the current density of the conductive element 22. Increasing the pitch of the coil (i.e. winding the coil less tightly) may decrease the current density of the conductive element. Decreasing the pitch may increase the current density of conductive element 22.

30 Preferably, the pitch or tightness of the coil of conductive element 22 may determine the flow rate of the irrigation fluid through the conductive element 22. Increasing the pitch of the coil (i.e. winding the coil less tightly) may increase the flow

rate of irrigation fluid through conductive element 22. Decreasing the pitch may decrease the flow rate of irrigation fluid through conductive element 22.

As seen in the embodiment of FIG. 6, the coil 22 may be a double coaxial, reverse-wound spring. This embodiment, for example, provides an increased resistance to fluid flow and nets a more even distribution along the length of the coil. Therefore, by varying the pitch of a conductive coil 22, characteristics of the lesion created along the length of the electrode may also be varied. Thus if a surgeon were to desire a shallower lesion at section F than at section G, he may use a variable pitch electrode as shown in FIG. 6. The decreased pitch at section f of electrode 22 may result in a lower rate of irrigation flow. This may create a shallower lesion at section F of the tissue. The increased pitch at section g of electrode 22 may result in a higher rate of irrigation flow. This may create a deeper lesion at section G of the tissue.

FIG. 7 shows a schematic view of a cross-section of a variable length electrode in accordance with the present invention. Conductive element 622 may be for example a double wound coil or spring as described above. Irrigating fluid may be flowed through the lumen 724 of electrode 722. Support element 733 may be for example a slotted tube. Such a slotted tube 733 may be any suitable material that may provide additional structural integrity to conductive element 722. The slotted tube 733 has an opening or slot 734. Preferably this opening 734 may run the length of an entire conductive element 722. This opening 734 may also run the length of an exposed section of a conductive element 722 which may be exposed in a manner as described in the above embodiments. This opening 734 may preferably face a surface of the tissue 760 to be ablated. As shown in FIG. 7, insulating material 732 may cover a portion of conductive element 760 rather than covering the entire conductive element 722. Insulating material 732 may be for example a microporous non-conductive component. Such a microporous non-conductive component may be manufactured from a material such as silicone, PTFE, Dacron fabric or solvent-precipitated polyurethane. Preferably, the pores in the microporous non-conductive component may be large enough to allow the free flow of irrigating fluid but small enough so as not to become clogged with protein or other detritus from the tissue to be irrigated. Irrigating fluid may flow from the lumen 724 of conductive element 722 in the manner indicated by the arrows.

FIG. 8 shows a schematic view of a cross-section of a second embodiment of a variable length electrode in accordance with the present invention. Conductive element **822** may be for example a double wound coil or spring as described above. Irrigating fluid may be flowed through the lumen **824** of electrode **822**. Support element **833** may be for example a slotted tube. Such a slotted tube **833** may be any suitable material that may provide additional structural integrity to conductive element **822**. The slotted tube **833** has an opening or slot **834**. Preferably this opening **834** may run the length of an entire conductive element **822**. This opening **834** may also run the length of an exposed section of a conductive element **822** which has been exposed in a manner as described in the above embodiments. This opening **834** may preferably face a surface of the tissue **860** to be ablated. As shown in **FIG. 8**, insulating material **832** may cover all of conductive element **822**. Insulating material **832** may also cover slotted tube **833**. Insulating material **832** may be for example a microporous non-conductive component. Such a microporous non-conductive component may be manufactured from a material such as silicone, PTFE, Dacron fabric or solvent-precipitated polyurethane. Preferably, the pores in the microporous non-conductive component may be large enough to allow the free flow of irrigating fluid but small enough so as not to become clogged with protein or other detritus from the tissue to be irrigated. Irrigating fluid may flow from the lumen **824** of conductive element **822** in the manner indicated by the arrows.

FIG. 9 shows a schematic view of a cross-section of a third embodiment of a variable length electrode in accordance with the present invention. Conductive element **922** may be a slotted tube that also serves as a support element. Irrigating fluid may be flowed through the lumen **924** of electrode **922**. The slotted tube **922** has an opening or slot **934**. Preferably this opening **934** may run the length of an entire conductive element **922**. This opening **934** may also run the length of an exposed section of a conductive element **922** which may be exposed in a manner as described in the above embodiments. This opening **934** may preferably face a surface of the tissue **960** to be ablated. As shown in **FIG. 9**, insulating material **932** may cover all of conductive element **922**. Insulating material **932** may be for example a microporous non-conductive component. Such a microporous non-conductive component may be manufactured from a material such as silicone, PTFE, Dacron fabric or solvent-precipitated polyurethane. Preferably, the pores

in the microporous non-conductive component may be large enough to allow the free flow of irrigating fluid but small enough so as not to become clogged with protein or other detritus from the tissue to be irrigated. Irrigating fluid may flow from the lumen 924 of conductive element 922 in the manner indicated by the arrows.

5 **FIG. 10** shows a schematic view of a cross-section of a fourth embodiment of a variable length electrode in accordance with the present invention. Conductive element 1022 may be, for example a conductive wire located in a non-porous tube 1040. Irrigating fluid may be flowed through the lumen 1024 of tube 1040. The non-porous tube 1040 may have a segment of insulating material 1032. Preferably this segment 1032 may run
10 the length of an entire conductive element 1022. This segment 1032 may also run the length of an exposed section of a conductive element 1022 which has been exposed in a manner as described in the above embodiments. This segment 1032 may preferably face a surface of the tissue 1060 to be ablated. Insulating material segment 1032 may be for
15 example a microporous non-conductive component. Such a microporous non-conductive component may be manufactured from a material such as silicone, PTFE, Dacron fabric or solvent-precipitated polyurethane. Preferably, the pores in the microporous non-conductive component may be large enough to allow the free flow of irrigating fluid but small enough so as not to become clogged with protein or other detritus from the tissue to be irrigated. Irrigating fluid may flow from the lumen 1024 of nonporous tube 1040 in the
20 manner indicated by the arrows.

FIG. 11 shows a schematic view of a cross-section of a fifth embodiment of a variable length electrode in accordance with the present invention. Conductive element 1122 may be, for example a conductive wire located in a non-porous tube 1140. Irrigating fluid may be flowed through the lumen 1124 of tube 1140. The non-porous tube 1140
25 may have a rigid segment 1132 of microporous non-conductive material. Preferably this segment 1132 may run the length of an entire conductive element 1122. This segment 1132 may also run the length of an exposed section of a conductive element 1122 which has been exposed in a manner as described in the above embodiments. This segment 1132 may preferably face a surface of the tissue 1160 to be ablated. Rigid segment 1132 may
30 be, for example, a microporous non-conductive component that is rigid. Such a microporous non-conductive component may be manufactured from a material such as rod

stock. Preferably, the pores in the microporous non-conductive component may be large enough to allow the free flow of irrigating fluid but small enough so as not to become clogged with protein or other detritus from the tissue to be irrigated. Irrigating fluid may flow from the lumen 1124 of nonporous tube 1140 in the manner indicated by the arrows.

5 **FIG. 12** shows a schematic view of a cross-section of a sixth embodiment of a variable length electrode in accordance with the present invention. Conductive element 1222 may be, for example a conductive wire located in a non-porous slotted tube 1233. Such a slotted tube 1233 may be any suitable material that may provide additional structural integrity to conductive element 1222. The slotted tube 1233 has an opening or
10 slot 1234. Preferably this opening 1234 may run the length of an entire conductive element 1222. This opening 1234 may also run the length of an exposed section of a conductive element 1222 which has been exposed in a manner as described in the above embodiments. This opening 1234 may preferably face a surface of the tissue 1260 to be ablated. The lumen 1224 of tube 1233 may be filled with a material 1250 that exudes
15 fluid such as, for example, a hydrogel. Irrigating fluid may be flowed through the hydrogel 1250 as described above. Alternatively, hydrogel 1250 may be saturated with irrigating fluid. When hydrogel 1250 contacts tissue 1260, gel 1250 may exude sufficient irrigating fluid. Tube 1233 may be for example a microporous non-conductive component that is rigid. Such a microporous non-conductive component may be manufactured from a
20 material such as rod stock. Preferably, the pores in the microporous non-conductive component may be large enough to allow the free flow of irrigating fluid but small enough so as not to become clogged with protein or other detritus from the tissue to be irrigated. Irrigating fluid may flow from the lumen 1224 of nonporous tube 1240 in the manner indicated by the arrows.

25 It is contemplated that the electrodes of the present invention may be used in a variety of ablation systems such as those available from Medtronic, Inc., Minneapolis, USA. It should be appreciated that the embodiments described above are to be considered in all respects only illustrative and not restrictive. The scope of the invention is indicated by the following claims rather than by the foregoing description. All changes that come
30 within the meaning and range of equivalents are to be embraced within their scope.

WE CLAIM:

- 5 1. A device for ablating organic tissue, comprising:
 a conductive element;
 a fluid component in communication with the conductive element; and
 an interface positioned adjacent the tissue to allow the fluid to pass through
the interface and contact the tissue.
- 10 2. The device of claim 1, wherein the conductive element is a metallic coil
with a lumen.
3. The device of claim 1, wherein the conductive element is a spring with a
lumen.
- 15 4. The device of claim 1, wherein the conductive element has a conductive
element diameter and the interface has an interface diameter, the conductive element
diameter being greater than the interface diameter.
- 20 5. The device of claim 1, wherein the interface has a length, the length being
variable.
6. The device of claim 1, wherein the interface is micro-porous.
- 25 7. The device of claim 1, wherein a portion of the interface may be removed
to expose the conductive element.
8. The device of claim 7, wherein the interface is perforated.
- 30 9. The device of claim 7, wherein the interface may be rotatably opened.

10. The device of claim 1, wherein the interface comprises openings that may be slidably opened.

5 11. The device of claim 1, wherein the interface is non-conductive.

12. The device of claim 1, wherein the interface is from the group consisting of: silicones, PTFE, Dacron fabrics, solvent-precipitated polyurethane micro-porous polymeric coatings, stainless steel nitinol, machining rod stock, polyester fabrics,
10 hydrogels and a gel.

13. The device of claim 1, wherein the interface lies between the conductive element and the surface of the tissue.

15 14. The device of claim 1, wherein the interface encircles the conductive element and the fluid component.

15. The device of claim 1, wherein the interface is conductive.

20 16. The device of claim 1, wherein the interface and the conductive element are the same.

17. The device of claim 1, wherein the conductive element is a wire, the wire located within the fluid component.

25 18. The device of claim 16, wherein the fluid component is a non-porous coating.

19. The device of claim 16, wherein the interface is a micro-porous section of the non-porous coating.

30

20. The device of claim 16, wherein the interface is a rigid structure.

21. The device of claim 16, wherein the interface is a fluid saturated gel.
22. The device of claim 20, wherein the interface and the fluid component are
5 the same.
23. The device of claim 1 further comprising:
means for flowing the fluid component through the interface.
24. The device of claim 1 further comprising:
10 an infusion pump in communication with the fluid component for flowing
the fluid component through the interface.
25. The device of claim 1 further comprising:
15 a maneuvering mechanism operably attached to the conductive element.
26. The device of claim 25, wherein the maneuvering mechanism is a
hemostat-type tool.
27. The device of claim 25, wherein the maneuvering mechanism is a catheter.
20
28. A device for ablating organic tissue comprising:
a conductive element; and
a hemostat-type tool, wherein the conductive element is placed adjacent at
25 least one jaw of the tool.
29. The device of claim 28, wherein the conductive element is a metallic coil
with a lumen.
30. The device of claim 28, wherein the conductive element is a spring with a
30 lumen.

- 5 31. A device for creating ablations of variable length, comprising:
 a conductive element having a channel formed therein;
 the channel operatively adapted to receive irrigating fluid; and
 a removable non-conductive interface in communication with the
conductive element.
32. The device of claim 31 further comprising:
 a support element in communication with the conductive element.
- 10 33. The device of claim 31, wherein the support element is a slotted tube.
34. The device of claim 31, wherein the conductive element is a slotted tube.
35. The device of claim 31 further comprising:
 a maneuvering mechanism operably attached to the conductive element.
- 15 36. The device of claim 31, wherein the maneuvering mechanism is a
hemostat-type tool.
37. The device of claim 31, wherein the maneuvering mechanism is a catheter.
- 20 38. A device for creating ablations of variable length, comprising:
 a non-porous tube operatively adapted to receive irrigating fluid therein;
 a conductive element in communication with the tube; and
 a removable non-conductive interface in communication with the
25 conductive element.
39. The device of claim 38, wherein the non-conductive interface is a portion
of the non-porous tube.
- 30 40. The device of claim 39, wherein the non-conductive interface is micro-
porous.

41. The device of claim 38, wherein the non-conductive interface is rigid.

42. The device of claim 38 further comprising:
a maneuvering mechanism operably attached to the conductive element.

43. The device of claim 38, wherein the maneuvering mechanism is a
hemostat-type tool.

44. The device of claim 38, wherein the maneuvering mechanism is a catheter.

45. A device for creating ablations of variable length, comprising:
a non-porous tube operatively adapted to receive a hydrogel;
a conductive element in communication with the tube; and
a removable non-conductive interface in communication with the
conductive element.

46. The device of claim 45, wherein the tube is slotted.

47. The device of claim 45 further comprising:
a maneuvering mechanism operably attached to the conductive element.

48. The device of claim 47, wherein the maneuvering mechanism is a
hemostat-type tool.

49. The device of claim 47, wherein the maneuvering mechanism is a catheter.

50. A method of ablating organic tissue, comprising:
providing a conductive element having a channel formed therein,
the channel operatively adapted to receive irrigating fluid; and
a removable non-conductive interface in communication with the
conductive element;

removing a portion of the interface to expose a portion of the conductive
element; and

ablating the tissue with the exposed portion of the conductive element.

5


51. The method of claim 50, wherein the interface is perforated.

52. The method of claim 50, wherein the interface is disposable.

53. The method of claim 50, wherein the interface is reusable.

10


54. The method of claim 50, wherein the interface is a removable tip.



10

FIG. 1

2/9







FIG. 3






FIG. 5

6/9




FIG. 6

7/9




FIG. 7








FIG. 8

8 / 9



9/9



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 November 2001 (08.11.2001)

PCT

(10) International Publication Number
WO 01/82813 A3

(51) International Patent Classification⁷: **A61B 18/14**

(21) International Application Number: **PCT/US01/12628**

(22) International Filing Date: **18 April 2001 (18.04.2001)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
09/558,975 27 April 2000 (27.04.2000) **US**

(71) Applicant: **MEDTRONIC, INC.** [US/US]; 710
Medtronic Parkway Northeast, Minneapolis, MN 55432
(US).

(72) Inventors: **FRANCISCHELLI, David, E.**; 744 Benton
Street, Anoka, MN 55303 (US). **COMBEN, Richard,**
H.; 2832 Woodcrest Drive, St. Paul, MN 55112 (US).
HOEY, Michael, F.; 5733 Pond Drive, Shoreview, MN
55126 (US). **MEHRA, Rahul**; 4980 Neal Avenue North,

Stillwater, MN 55082 (US). **OCEL, Jon, M.**; 573 10th
Avenue S.W., New Brighton, MN 55112 (US). **PEAR-**
SON, Robert; 2134 Wallingford Lane, Woodbury, MN
55125 (US). **TRESCONY, Paul, V.**; 11648 Oakview
Court, Champlin, MN 55316 (US). **JAHNS, Scott, E.**;
923 3rd Street, Hudson, WI 54016 (US).


(74) Agent: **BAUER, Stephen, W.**; Medtronic, Inc. LC340,
710 Medtronic Parkway, Minneapolis, MN 55432 (US).

(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,
DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,
UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **VARIABLE LENGTH ELECTRODES FOR DELIVERY OF IRRIGATED ABLATION**



10

(57) Abstract: A device for ablating tissue is provided. The device comprises a conductive element with a channel for irrigating fluid formed therein, which is in contact with a non-conductive microporous interface. All or a portion of the interface may be removable. When the interface is removed, a portion of the conductive element is exposed for use in ablating tissue. Methods of using the device and for removing the interface are also provided.



WO 01/82813 A3



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the international search report:

11 April 2002

INTERNATIONAL SEARCH REPORT

International Application No

PCT/JS 01/12628

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B18/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99 03414 A (MEDTRONIC INC) 28 January 1999 (1999-01-28) summary of invention, description fig 6 figure 4 ---	1,16,20, 28
X	US 6 015 407 A (FOSSE LORNA ET AL) 18 January 2000 (2000-01-18) column 3, line 20 -column 4, line 14 column 5, line 50-57 column 5, line 25-35 ---	1,6,8, 11-14,17
X	US 6 010 500 A (RIEB DALE ET AL) 4 January 2000 (2000-01-04) summary of the invention column 6, line 33-45 --- -/--	1,10

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

24 September 2001

Date of mailing of the international search report

08.02.02

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

PAPONE, F

INTERNATIONAL SEARCH REPORT

International Application No

PC: JS 01/12628

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 041 260 A (STERN ROGER A ET AL) 21 March 2000 (2000-03-21) column 4, line 56 -column 5, line 7 ---	1,18,21, 22,25
X	US 5 569 242 A (FANTON GARY S ET AL) 29 October 1996 (1996-10-29) column 4, line 25-40 column 8, line 45 -column 9, line 8 ---	1,23,24
X	US 5 895 417 A (ANDERSON STEVEN C ET AL) 20 April 1999 (1999-04-20) description fig 4 figure 4 ---	1-3,29, 30
A	US 5 919 188 A (MAGUIRE MARK A ET AL) 6 July 1999 (1999-07-06) description fig 5 -----	1,10

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 01/12628

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 50-54
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:
1-30

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-30

an ablation effector having a conductive element, a fluid component, and an interface allowing fluid passage

2. Claims: 31-49

an ablation effector having a conductive element with a lumen allowing fluid passage and a removable non conductive interface

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PC^{*} IS 01/12628

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9903414	A	28-01-1999	AU 1645499 A	10-02-1999
			EP 0996380 A1	03-05-2000
			WO 9903414 A1	28-01-1999

US 6015407	A	18-01-2000	US 5800482 A	01-09-1998
			WO 9948421 A1	30-09-1999
			DE 69610566 D1	09-11-2000
			DE 69610566 T2	28-06-2001
			EP 0884978 A1	23-12-1998
			JP 2000506751 T	06-06-2000
			WO 9732525 A1	12-09-1997
			US 6119041 A	12-09-2000
			US 6032077 A	29-02-2000
			US 5895417 A	20-04-1999

US 6010500	A	04-01-2000	NONE	

US 6041260	A	21-03-2000	US 5443470 A	22-08-1995
			US 5277201 A	11-01-1994
			AU 6625594 A	08-11-1994
			CA 2159483 A1	27-10-1994
			EP 0693955 A1	31-01-1996
			JP 8508912 T	24-09-1996
			WO 9423794 A1	27-10-1994
			US 5562720 A	08-10-1996
			US 5713942 A	03-02-1998
			AT 164503 T	15-04-1998
			AU 4105293 A	29-11-1993
			CA 2117900 A1	11-11-1993
			DE 69317776 D1	07-05-1998
			DE 69317776 T2	10-09-1998
			EP 0637943 A1	15-02-1995
			FI 945112 A	31-10-1994
			IL 105523 A	10-01-1997
			JP 7506033 T	06-07-1995
			NO 944072 A	26-10-1994
			WO 9321846 A1	11-11-1993
			US 5443463 A	22-08-1995

US 5569242	A	29-10-1996	US 5458596 A	17-10-1995
			US 6277116 B1	21-08-2001
			AT 206029 T	15-10-2001
			AU 715173 B2	20-01-2000
			AU 2432195 A	29-11-1995
			CA 2188668 A1	16-11-1995
			DE 69522939 D1	31-10-2001
			EP 0760626 A1	12-03-1997
			JP 10504732 T	12-05-1998
			WO 9530373 A1	16-11-1995

US 5895417	A	20-04-1999	US 5800482 A	01-09-1998
			DE 69610566 D1	09-11-2000
			DE 69610566 T2	28-06-2001
			EP 0884978 A1	23-12-1998
			JP 2000506751 T	06-06-2000
			US 6015407 A	18-01-2000
			WO 9732525 A1	12-09-1997
			US 6119041 A	12-09-2000

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PC./US 01/12628

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5895417	A	US 6032077 A	29-02-2000
US 5919188	A	06-07-1999	NONE

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.